

RC-RADAR		죽산1교(상) 철근탐사 자료						
PROJECT TITLE		국도45호선 도곡2교 등 3개소 정밀안전점검 및 내진성능평가용역						
Company		(주)명성엔지니어링			Client		수원국토관리사무소	
시험 결과								
No	위치	철근방향	실측 배근간격 (mm)	설계 배근간격 (mm)	실측 피복두께 (mm)	설계 피복두께 (mm)	비고	
1	S1 바닥판하면	주철근	130	148	74	40	양호	
		배력철근	192	200	44	40	양호	
2	S2 바닥판하면	주철근	125	148	67	40	양호	
		배력철근	194	200	44	40	양호	
3	S3 바닥판하면	주철근	120	148	74	40	양호	
		배력철근	194	200	44	40	양호	
4	S4 바닥판하면	주철근	133	148	69	40	양호	
		배력철근	180	200	44	40	양호	
5	S5 바닥판하면	주철근	130	148	72	40	양호	
		배력철근	190	200	47	40	양호	
6	S6 바닥판하면	주철근	120	148	72	40	양호	
		배력철근	198	200	52	40	양호	
7	S7 바닥판하면	주철근	130	148	67	40	양호	
		배력철근	195	200	52	40	양호	
8	P2 교각 코핑	수직철근	146	150	89	100	양호	
		수평철근	275	300	86	100	양호	
9	P3 교각 코핑	수직철근	152	150	86	100	양호	
		수평철근	288	300	82	100	양호	
10	P4 교각 코핑	수직철근	149	150	96	100	양호	
		수평철근	305	300	79	100	양호	
11	P5 교각 코핑	수직철근	148	150	100	100	양호	
		수평철근	275	300	82	100	양호	
12	P6 교각 코핑	수직철근	145	150	96	100	양호	
		수평철근	280	300	82	100	양호	







