

-12.0	0.0	0.0	-330.4	330.4	
		W-LO	I	0.0	
-25.7	0.0	-77.1	77.1	0.0	0.0
		J	0.0	0.0	-31.4
0.0	-461.8	461.8	0.0	0.0	

BEAM ELEMENT STRESSES MIN/MAX SUMMARY BY
PROPERTY PRINTOUT Unit System : kN , m

[SECTION NAME : 코핑1 , SECTION ID : 1 , SECTION
SHAPE : SB]
[SECTION SIZE] H:1.527 B:2.8
** MAX

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
1 AXL	D	1 J	0.0	0.0
75.4	0.0	202.4	-202.4	
6 SHY	W-LO	1 I	0.0	7.3
0.0	-10.7	10.7	0.0	
1 SHZ	D	1 J	0.0	0.0
75.4	0.0	202.4	-202.4	
1 BY+	D	1 I	0.0	0.0
0.0	0.0	0.0	0.0	
1 BY-	W-LO	1 J	0.0	-7.3
0.0	-10.7	10.7	0.0	
1 BZ+	D	1 J	0.0	0.0
75.4	0.0	202.4	-202.4	
1 BZ-	D	1 I	0.0	0.0
0.0	0.0	0.0	0.0	

** MIN

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
1 AXL	W-TR	1 I	-6.2	0.0
0.0	0.0	0.0	0.0	
1 SHY	W-LO	1 J	0.0	-7.3
0.0	-10.7	10.7	0.0	
6 SHZ	D	1 I	0.0	0.0
-75.4	0.0	202.4	-202.4	
1 BY+	W-LO	1 J	0.0	-7.3
0.0	-10.7	10.7	0.0	
1 BY-	W-TR	1 I	-6.2	0.0
0.0	0.0	0.0	0.0	
1 BZ+	W-TR	1 I	-6.2	0.0
0.0	0.0	0.0	0.0	
1 BZ-	D	1 J	0.0	0.0
75.4	0.0	202.4	-202.4	

[SECTION NAME : 코핑2 , SECTION ID : 2 , SECTION
SHAPE : SB]
[SECTION SIZE] H:2.231 B:2.8
** MAX

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
5 AXL	W-TR	1 I	42.2	0.0
0.0	0.0	351.1	-351.1	
5 SHY	W-LO	1 I	0.0	11.0
0.0	-33.0	33.0	0.0	
2 SHZ	D	1 J	0.0	0.0
1032.7	0.0	4093.8	-4093.8	
5 BY+	W-TR	1 I	42.2	0.0
0.0	0.0	351.1	-351.1	
2 BY-	W-LO	1 J	0.0	-11.0
0.0	-33.0	33.0	0.0	
2 BZ+	D	1 J	0.0	0.0
1032.7	0.0	4093.8	-4093.8	
2 BZ-	W-TR	1 I	-46.5	0.0
0.0	0.0	-351.1	351.1	

** MIN

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
2 AXL	W-TR	1 I	-46.5	0.0
0.0	0.0	-351.1	351.1	

2 SHY	W-LO	1 J	0.0	-11.0
0.0	-33.0	33.0	0.0	
5 SHZ	D	1 I	0.0	0.0
-962.4	0.0	0.0	3810.3	-3810.3
2 BY+	W-LO	1 J	0.0	-11.0
0.0	-33.0	33.0	0.0	
2 BY-	W-TR	1 I	-46.5	0.0
0.0	0.0	0.0	-351.1	351.1
2 BZ+	W-TR	1 I	-46.5	0.0
0.0	0.0	0.0	-351.1	351.1
2 BZ-	D	1 J	0.0	0.0
1032.7	0.0	0.0	4093.8	-4093.8

[SECTION NAME : 코핑3 , SECTION ID : 3 , SECTION
SHAPE : SB]
[SECTION SIZE] H:3 B:2.8
** MAX

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
4 AXL	W-TR	1 J	31.4	0.0
0.0	0.0	0.0	194.2	-194.2
4 SHY	W-LO	1 I	0.0	12.2
0.0	-46.4	46.4	0.0	
3 SHZ	D	1 J	0.0	0.0
823.1	0.0	0.0	3855.2	-3855.2
4 BY+	W-TR	1 I	31.4	0.0
0.0	0.0	0.0	194.2	-194.2
3 BY-	W-LO	1 J	0.0	-12.2
0.0	-46.4	46.4	0.0	
3 BZ+	D	1 J	0.0	0.0
823.1	0.0	0.0	3855.2	-3855.2
3 BZ-	W-TR	1 I	-34.6	0.0
0.0	0.0	0.0	-194.2	194.2

** MIN

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
3 AXL	W-TR	1 I	-34.6	0.0
0.0	0.0	0.0	-194.2	194.2
3 SHY	W-LO	1 J	0.0	-12.2
0.0	-46.4	46.4	0.0	
4 SHZ	D	1 I	0.0	0.0
-770.9	0.0	0.0	3593.9	-3593.9
3 BY+	W-LO	1 J	0.0	-12.2
0.0	-46.4	46.4	0.0	
3 BY-	W-TR	1 I	-34.6	0.0
0.0	0.0	0.0	-194.2	194.2
3 BZ+	W-TR	1 I	-34.6	0.0
0.0	0.0	0.0	-194.2	194.2
3 BZ-	D	1 J	0.0	0.0
823.1	0.0	0.0	3855.2	-3855.2

[SECTION NAME : 기둥 , SECTION ID : 4 , SECTION
SHAPE : SR]
[SECTION SIZE] D:3
** MAX

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
7 AXL	W-TR	1 J	0.0	0.0
-110.3	0.0	0.0	-2375.7	2375.7
7 SHY	D	1 I	-1262.8	0.0
0.0	0.0	0.0	414.0	-414.0
7 SHZ	D	1 I	-1262.8	0.0
0.0	0.0	0.0	414.0	-414.0
7 BY+	W-TR	1 I	0.0	0.0
-104.6	0.0	0.0	-929.0	929.0
7 BY-	W-LO	1 J	0.0	-31.4
0.0	-461.8	461.8	0.0	
7 BZ+	D	1 I	-1262.8	0.0
0.0	0.0	0.0	414.0	-414.0
7 BZ-	W-TR	1 J	0.0	0.0
-110.3	0.0	0.0	-2375.7	2375.7

** MIN

ELEM COM	LC	PT	AXIAL	SHEAR-y
SHEAR-Z	(+y)-BENDING-(-y)	(+z)-BENDING-(-z)		
7 AXL	D	1 J	-1427.9	0.0
0.0	0.0	0.0	414.0	-414.0
7 SHY	W-LO	1 J	0.0	-31.4
0.0	-461.8	461.8	0.0	
7 SHZ	W-TR	1 J	0.0	0.0
-110.3	0.0	0.0	-2375.7	2375.7
7 BY+	W-LO	1 J	0.0	-31.4
0.0	-461.8	461.8	0.0	
7 BY-	D	1 J	-1427.9	0.0